

DUALCOOL AI AIR



• Combinación Única

MODELO			VA122C5	VA122H5	VA182C5	VA182H5	VA242C5	VA242H5
Capacidad de Enfriamiento	kW		3.52	3.52	5.27	5.27	6.45	6.45
	Btu/h		12,000	12,000	18,000	18,000	22,000	22,000
Capacidad de Calefacción	kW		-	3.52	-	5.3	-	6.4
	Btu/h		-	12,000	-	18,000	-	22,000
Potencia de Entrada	Enfriamiento / Calefacción	W/W	920	940 / 830	1,503	1,560 / 1,460	1,940	1,940 / 1,840
Corriente	Enfriamiento / Calefacción	Btu/h	4.2	4.2 / 3.7	6.6	6.9 / 6.5	8.6	8.6 / 8.1
Corriente Máxima	Enfriamiento / Calefacción	W/W	-	3.7	-	6.5	-	8.1
EER			3.82	3.74	3.51	3.38	3.32	3.32
			13.0	12.8	12.0	11.5	11.3	11.3
COP			-	4.24	-	3.61	-	3.5
SEER			21.8	21.8	21.6	21.6	21.5	21.5
Suministro de Potencia	Ø, V,		1, 220, 50/60	1, 220, 50/60	1, 220, 50/60	1, 220, 50/60	1, 220, 50/60	1, 220, 50/60
Nivel de Ruido	Unidad Interior	Hz	48 / 42 / 35 / 27 / 19	- / 46 / 35 / 27 / 21	49 / 44 / 39 / 34 / 29	- / 48 / 41 / 36 / 32	51 / 47 / 42 / 34 / 31	- / 49 / 42 / 38 / 31
	Unidad Exterior	dB(A)	51	-	54	-	55	-
Compresor	Tipo	dB(A)	Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
Ventilador (interior)	Tipo de Motor		BLDC	BLDC	BLDC	BLDC	BLDC	BLDC
	Salida del Motor	W	30	30	30	30	30	30
Ventilador (exterior)	Tipo de Motor		BLDC	BLDC	BLDC	BLDC	BLDC	BLDC
	Salida del Motor	W	43	43	43	43	85	85
Dimensiones	Unidad Interior	mm	799 x 307 x 235	799 x 307 x 235	895 x 307 x 235	895 x 307 x 235	895 x 307 x 235	895 x 307 x 235
	(A x L x P)	inch	31.5 x 12.1 x 9.3	31.5 x 12.1 x 9.3	35.2 x 12.1 x 9.3	35.2 x 12.1 x 9.3	35.2 x 12.1 x 9.3	35.2 x 12.1 x 9.3
	Unidad Exterior	mm	717 x 483 x 230	717 x 483 x 230	770 x 545 x 288	770 x 545 x 288	870 x 650 x 330	870 x 650 x 330
	(A x L x P)	inch	28.2 x 19.0 x 9.1	28.2 x 19.0 x 9.1	30.3 x 21.5 x 11.3	30.3 x 21.5 x 11.3	34.3 x 25.6 x 13.0	34.3 x 25.6 x 13.0
Peso Neto	Unidad Interior	kg(lbs)	10.0 (22.0)	10.0 (22.0)	12.8 (28.2)	12.8 (28.2)	12.8 (28.2)	12.8 (28.2)
	Unidad Exterior	kg(lbs)	24.6 (54.2)	24.6 (54.2)	27.2 (59.9)	27.2 (59.9)	37.6 (82.9)	37.6 (82.9)
Rango de Operación	Enfriamiento	°C(°F)	-15 ~ 48°C (5 ~ 118.4°F)	-5 ~ 48°C (41 ~ 118.4°F)	-15 ~ 48°C (5 ~ 118.4°F)	-5 ~ 48°C (41 ~ 118.4°F)	-15 ~ 48°C (5 ~ 118.4°F)	-5 ~ 48°C (41 ~ 118.4°F)
	Calefacción	°C(°F)	-	-15 ~ 24°C (23 ~ 75.2°F)	-	-15 ~ 24°C (23 ~ 75.2°F)	-	-15 ~ 24°C (23 ~ 75.2°F)
Máx. Longitud de la tubería		m(ft)	15 (49.2)	15 (49.2)	20 (65.6)	20 (65.6)	20 (65.6)	20 (65.6)
Máx. Diferencia de elevación		m(ft)	7 (23.0)	7 (23.0)	10 (32.8)	10 (32.8)	10 (32.8)	10 (32.8)
Código de Herramienta (Chasis)	Unidad Interior + Unidad Exterior		S1 + U12A	S1 + U12A	S1 + U18A	S1 + U18A	S1 + U24A	S1 + U24A
Filtro	Pre Filtro (Lavable/Anti-hongos)		0	0	0	0	0	0
	Plasmaster Ionizer		0	0	0	0	0	0
	Limpieza Automática		0	0	0	0	0	0
Función	Rango para Ajuste de Temperatura	Enfriamiento	18 ~ 30°C (64 ~ 86°F)	18 ~ 30°C (64 ~ 86°F)	18 ~ 30°C (64 ~ 86°F)	18 ~ 30°C (64 ~ 86°F)	18 ~ 30°C (64 ~ 86°F)	18 ~ 30°C (64 ~ 86°F)
		Calefacción	-	-	-	-	-	-
	Modo Sueño		12 h	12 h	12 h	12 h	12 h	12 h
	Operación Soft Dry		0	0	0	0	0	0
	Jet Cool		0	0	0	0	0	0
	Control Wi-Fi (Control por Smartphone)		0	0	0	0	0	0
	Protección para Voltaje		0	0	0	0	0	0
	Smart Diagnosis		0	0	0	0	0	0

※ Las especificaciones, el diseño y las características están sujetos a cambios sin previo aviso.