

MULTI

CASSETTE 1 VÍA

SOLO FRIO			
kBtu/h	9	12	18
kW	2.6	3.5	5.3
Cassette 1 Vía	ZMNQ09GTUA1	ZMNQ12GTUA1	ZMNQ18GTTA1

Unidad				ZMNQ09GTUA1	ZMNQ12GTUA1	ZMNQ18GTTA1
Capacidad	Enfriamiento	Nom	kW	2.6	3.5	5.3
Potencia de Entrada		Nom	W	20	20	30
Corriente		Nom	A	0.2	0.2	0.31
Suministro de Potencia			Ø, V, Hz	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60
Flujo de Aire		A / M / B	m³/min	7.5 / 7.3 / 6.8	8.1 / 7.4 / 7.0	13.5 / 11.3 / 10.1
Nivel de Ruido	Enfriamiento	A / M / B	dB(A)	36 / 34 / 32	37 / 36 / 33	44 / 42 / 39
Potencia Sonora	Enfriamiento	Máx	dB(A)	54	57	59
Dimensiones	Cuerpo	A x L x P	mm	860 x 132 x 450	860 x 132 x 450	1,180 x 132 x 450
Peso	Cuerpo		kg	11.7	11.7	14.5
Conexiones de Tubería	Líquido		mm(pulg)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas		mm(pulg)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)
Panel Decorativo	Modelo			PT-UPHG0	PT-UPHG0	PT-TPHG0
	Color			Blanco (RAL 9003)	Blanco (RAL 9003)	Blanco (RAL 9003)
	Dimensiones	A x L x P	mm	1,160 x 34 x 500	1,160 x 34 x 500	1,480 x 34 x 500
	Peso		kg	4.1	4.1	4.9
Control Remoto				○ / Inalámbrico	○ / Inalámbrico	○ / Inalámbrico
Kit de purificación						