

SOLO FRIO					
kBtu/h	7	9	12	18	24
kW	2.0	2.6	3.5	5.3	7.0
Unidades Montadas en Muro  Estándar					
	ZMNQ07GSJA1	ZMNQ09GSJA1	ZMNQ12GSJA1	ZMNQ18GSKA1	ZMNQ24GSKA1

• Estándar

MODELO				ZMNQ07GSJA1	ZMNQ09GSJA1	ZMNQ12GSJA1	ZMNQ18GSKA1	ZMNQ24GSKA1
Capacidad	Enfriamiento	Nom	kW	2.1	2.5	3.5	5.0	6.6
Potencia de	Entrada	Nom	W	17	18	19	39	45
Corriente		Nom	A	0.15	0.16	0.17	0.28	0.33
Suministro de Potencia		Ø, V, Hz		1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60	1, 220 ~ 240, 50/60
Flujo de Aire		A / M / B	m³/min	7.5 / 6.1 / 4.9	9.2 / 7.4 / 5.6	9.6 / 8.1 / 5.6	14.2 / 11.3 / 9.9	15.2 / 12.7 / 10.2
Nivel de Ruido		A / M / B	dB(A)	35 / 31 / 26	36 / 33 / 27	40 / 35 / 27	44 / 38 / 35	46 / 41 / 36
Potencia Sonora			dB(A)	56	57	57	59	65
Dimensiones		A x L x P	mm	837 x 308 x 189	837 x 308 x 189	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210
Peso			kg	8.3	8.5	8.5	11.6	12.5
Conexiones de Tubería	Líquido		mm(pulg)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas		mm(pulg)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)
Control Remoto				○ / Inalámbrico	○ / Inalámbrico	○ / Inalámbrico	○ / Inalámbrico	○ / Inalámbrico
Kit de purificación				-	-	-	-	-